



TRIPLE SPUR GEAR CHAIN PULLEY BLOCK MODEL P



- ▶ ISI Marked Manufactured in ISO 9001 : 2000 certified company
Assured quality & interchangeability of parts
- ▶ Tested as per ISI procedure for 50% over load
Assured safety
- ▶ Grade 80 load chain & zinc plated hand chain
Longer chain life
- ▶ Rugged German design, in use for more than 30 years
Assured reliability
- ▶ Double ball bearing supported load wheel
Smooth operation
- ▶ Precision machine case hardened alloy steel gears
Long life, noiseless operation
- ▶ Fully pocketed S.G. iron cast load chain wheel
Long life, safe and smooth running
- ▶ Anti corrosive powder coated zinc plated parts
Anti rust & better aesthetics

ISO AVAILABLE
Light Weight Model,
Shock Proof,
Pulley


TRIPLE SPUR GEAR CHAIN PULLEY BLOCK - MODEL P

SPECIFICATIONS / DIMENSIONS (mm)

Capacity	MT	0.5	1	2	3	5	7.5	10
No. of falls		1	1	2	2	2	3	4
Running pull on hand chain	Kgs.	13	26	28	43	49	50	61
Weight at 3 metre lift (approx.)	Kgs.	21	21	30	35	60	88	126
Extra weight per additional metre lift (approx.)	Kgs.	2.9	2.9	4.3	4.3	5.2	7.0	14.4

Capacity MT	A	B	C	D	E	F	H	Mono blocks (not shown) H	Thrust bearing in bottom block H
0.5 T	460	210	180	210	195	31	550	500	580
1 T	460	210	180	210	195	31	550	500	580
2 T	560	240	180	210	195	37	665	620	760
3 T	625	240	200	210	195	42	759	635	825
5 T	810	320	225	275	270	51	885	780	1010
7.5 T	910	455	225	275	270	75	1017	952	1135
10 T	990	515	225	275	270	75	1120	1025	1240

All dimensions in mm.
Data tolerance \pm 10%.



CODE NO 41 : DO : 1760/LT/CPB (INDEF-P) /11-2014

rasam.87@gmail.com

HERCULES HOISTS LIMITED

HERCULES HOISTS LTD.
8, Camac Street,
2nd Floor, Room No-7
Kolkata-700017

43/2B, Savroli-Kharpada Road
Dhamani, Khalapur - 410 202

Maharashtra, India

☎ : +91 2192 274601/605

☎ : +91 2192 274325

✉ : indef@indef.com

haiji group